



DI/MX150D3CSB027 Moris Distributor Block 15 – 150 l / min



DI/MX150D3CSB027 Moris distributor block 15 – 150 l / min (adjusted at 150 l/min), direct starting, dual voltage coil (on EB), Max operating pressure 35 bars and min operating pressure 19 bars

- n°1 – SOFT STOP 250 block with soft / stop solenoid valve complete with Reg.21, without coil, up to 250 l / min
- n°1 – BOB / B048 / 12DV – dual voltage coil (voltage: 48 + 12 v) – supplied without connector and connection cable
- n°2 – BOB / M048DV – single voltage coil (voltage: 48 v) – supplied without connector and connection cable
- n°3 – 5043/1 – connector and cable for 48 VDC coil connection
- n°1 – 5043/2 – connector and cable for 12 VDC emergency connection for dual voltage coil

Photo gallery



MPPR Sp. z o.o.

ul. Kolejowa 11/13, 01-217
Warszawa
NIP: PL5272974730
Tel: +48 22 631 22 83
mppr@op.pl

Biuro

Tel: +48 600 826 485
biuro@mppr.com.pl

Sprzedaz i marketing

Marcin Nasiadek
Tel: +48 668 592 976
admin@mppr.com.pl

Finanse i faktury

Krzysztof Ząbek
Tel: +48 22 631 22 83
zabek@mppr.com.pl