

Specifications

Photo is representative

Eaton DILM32-10(RDC60)

Eaton XT IEC mini contactor, 32A, 60 Vdc, 1NO, 32A, Frame C, 45 mm, 2, 5/ 10, 10, 20, 25 (1/3PH @120, 240/208, 240, 480, 600 V), Three-pole, Reversing, XT IEC series, Full voltage reversing miniature contactor, 400V, 15 kW

General specifications

PRODUCT NAME	Eaton XT IEC mini contactor
CATALOG NUMBER	DILM32-10(RDC60)
EAN	4015082772758
PRODUCT LENGTH/DEPTH	2 in
PRODUCT HEIGHT	3.5 in
PRODUCT WIDTH	4 in
PRODUCT WEIGHT	1 lb
COMPLIANCES	RoHS Compliant CE Marked
CERTIFICATIONS	UL Listed CSA Certified IEC 60947 EN 60947

Product specifications

AMPERAGE RATING	32A
HP RATING - MAX	2, 5/ 10, 10, 20, 25 (1/3PH @120,240/208,240,480,600 V)
NUMBER OF POLES	Three-pole
TYPE	Full voltage reversing miniature contactor
VOLTAGE RATING	400 V
FRAME SIZE	45 mm
COIL VOLTAGE	60 Vdc
CONTACT CONFIGURATION	1 NO
CONTINUOUS AMPERE RATING	32 A
SERIES	XT IEC
OPERATION	Reversing
POWER CONSUMPTION	15 kW

Resources

	Contactors Explained
MULTIMEDIA	S1. E4. Ask the Experts - NEMA, IEC and DP contactors
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - DILM32-10(RDC60)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

